



## 11<sup>th</sup> GISFI Standardisation Series Meeting:

### Introducing 5G Standardisation

#### Prof Ramjee Prasad, Fellow IEEE, IET, IETE Founding Chairman, GISFI, www.gisfi.org

Bangalore, India, 17-12-2012



Center For TeleInFrastruktur • Aalborg University • Niels Jernes Vej 12 • 9220 Aalborg Ø • Denmark • www.ctif.aau.dk





**Innovative Communications** 



- Need systems that offer <u>human-centric</u> <u>ubiquitous</u> <u>terabit wireless</u> connectivity that will enable the humancentric mega-communication applications over the network of the future.
- The aim is to let people seamlessly bridge the virtual and physical worlds offering the same level of allsenses, context-based, rich communication experience over fixed and wireless networks.





# WISDOM: Revolutionarizing Telecommunication Concepts

 Wireless Innovative System for Dynamic Operating MegaCommunications (WISDOM) is a communication system for ubiqitous trustworthy human-centric connectivity via an arbitrary infrastructure support







## WISDOM Design Approach

WISDOM			
Information Theoretic Performance/Capacity Estimation		End-to-end Performance Optimization	Cognitive Networking Principles
Pillars of the WISDOM			

Center For TeleInFrastruktur • Aalborg University • Niels Jernes Vej 12 • 9220 Aalborg Ø • Denmark • www.ctif.aau.dk











Metro core network is permutation of WISDOM Mesh Network and WISDOM Edge Node.







#### **Architectural Challenges**

- Defficiencies of current architectural solutions
  - Centralised design does not allow for flexible topology reconfiguration and efficient spectrum resource utilisation.
  - Monolithic radio access and protocol architectures
  - Any evolving /optimising solution leads to higher costs and management complexity
  - Rigidness of spectrum regulation and usage: frequency bands are pre-allocated withou a consideration of the spectrum utilisation degree'



## Architectural Challenges



#### Design and Architectural Considerations

- How to design an architecture that will support autonomic behavior?
- How to represent the information necessary to an autonomic object in a wireless scenario to achieve an autonomic behavior?
- How wireless autonomic object communicate together, and organize among themselves in a possibly large context?







#### **Protocol Challenges**

- Novel approach to protocols: holistic protocol stack
- Routing, mobility, communication should be revisited:
  - Satisfy multiple, diverse and conflicting traffic flows requirements- <u>requires novel routing techniques</u>
  - Maintain end-to-end path quality subject to available spectrum and link *performance-requires proactive* <u>QoS techniques</u>
  - Coordinated channel usage and better spectrum exploitation: <u>novel resource allocation techniques</u>



# Other Challenges to be Addressed

- How to deal with an non-uniformly distributed digital world
- Trust, privacy, confidence
- How to deploy Internet technologies fully across the economy
- Main challenge:
  - How to be able to fully capitalize on the research innovations?